

BASIC / FLIP DELUXE MODELS



BASIC MODEL

Available in the following colors:

ABOUT

Limb Ninja Brush Cutters are designed for high performance cutting of vegetation, saplings and over hanging limbs on hunting lanes, roads and driveways. With a vertical cut of limbs as high as your tractor will reach. This unit is mounted on a skid steer quick attach plate or a John Deere Pin or Euro Global plate (or a combination Skid Steer and John Deere Pin).Please specify when you order. This unit is available in two models – BASIC (cuts vertical only) and FLIP DELUXE (cuts vertical and horizontal).

FEATURES

- Belt cover on all models for safety.
- Belt drive to prevent damage to motor if it hits something too big to cut
- Dual blades for kickback
- Deck construction is made out of 1/8" steel plate and 3/16" angle iron on deck for reinforcement
- All quick attach plates are made from 1/4" steel
- Each Limb Ninja is adjustable from side to side to fit the width of a compact tractor, full size tractor or a skid steer
- Weight is less than 400 lbs.
- · Blade protrudes 3" out in front of the deck for better cutting

COMPATIBILITY

- Any tractor or skid steer with 8.5 to 15 GPM's with rear remotes or
- 3rd function valve
- Skid Steer will require low flow switch or a flow control valve
- Hydraulic cylinder kit available on Flip Deluxe Model.
- PTO Pump and Hydraulic Tank also available

DETAILS

- Will work with any tractor that has quick attach hook ups (Specify which quick attach when you order)
- The first residential/small farm unit available for cutting vertically or horizontal with the Flip Deluxe Model
- Easily cuts 2-3" limbs, underbrush and around the edge of the slopes
- Many options available for connecting to existing tractor and skid steer
- Parts list available
- One Year Warranty on motor and other parts are considered wear parts and depending on the use of/ how the equipment is used
- 44" cutting width



FLIP DELUXE MODEL



FLIP DELUXE MODEL W/ PTO PUMP



FLIP DELUXE MODEL

CALL 334-791-2804 WWW.LIMBNINJA.COM



LIMB NINJA SPECIFICATIONS CHART

SPECIFICATION	BASIC MODEL	FLIP DELUXE MODEL
Cut Angle	Vertical Only	Vertical & Horizontal
Hydraulic Flow	8.5 to 15 GPMs	8.5 to 15 GPMs
Weight	400 lbs.	400 lbs.
Dimensions	45D x 52H x 76W (inches)	45D x 52H x 76W (inches)
Cutting Width	44"	44"
Cutting Diameter (limb size)	2-3"	2-3"
Deck Construction	1/8" steel plate w/ 3/16" angle iron on deck for reinforcement	1/8" steel plate w/ 3/16" angle iron on deck for reinforcement
Blade	2, double-sided	2, double-sided
Loader Requirement	Skid Steer, John Deere Pin, Euro Global, Combination Skid Steer and John Deere Pin	Skid Steer, John Deere Pin, Euro Global, Combination Skid Steer and John Deere Pin
Cutting Deck Adjustment	Not Available – Vertical Cutting Only	Can cut vertically or horizontally - Manual Adjustment – Chain - Automatic Adjustment – Hydraulic

SPECIAL NOTES:

- Cutting Deck Adjustment The Basic Model will cut vertical only. The Flip Deluxe Model will cut vertical and horizontal. You can adjust the position of how you want to cut manually using the chain or you can add the optional cylinder kit to make the cutting deck adjust to different cutting angles using hydraulics.
- PTO Pump & Hydraulic Tank A PTO pump & hydraulic tanks are available for smaller tractors.
- Unit Adjustment Each unit is adjustable side-to-side so that you can extend cutting deck out past front tire of tractor.
- Optional Flow Control Valve An optional flow control valve is needed for skid steer or high flow machine.

